

First step concentrate in a two step truckwash cleaning system to be followed by Anti-Static B. This is a concentrate for distributors to blend for resale to end users. When used as a two step cleaning system it will remove oily soils and help break static bond that causes dirt to cling to painted surfaces. For use by cleaning contractors and other cleaning professionals.



Where To Use

Truck fleets Tractor trailers Aluminum truck bodies

Dilution

For Stock product – 1/3

Directions

Anti-Static A and Anti-Static B should never be mixed together. This product is concentrated and must be diluted at 1/3 before running through pressure washer at 1/25 with cold water. Check the machine manufacturer's recommendations as to suitability of pressure washer for acid use. Otherwise acid must be injected with a down stream injector. Avoid applying on windy days and, before washing, always check suitability for use on surface to be cleaned. It is always best to wash from the bottom up. After applying dilution Anti-Static A follow with application of diluted Anti-Static B at proper dilution, and finally, pressure rinse clean with cold water pressure washer. Care should be taken on all glass surfaces. Do Not allow to dry on glass. When diluting always add acid to water and not vice versa.

Technical Specifications

COLOR: Transparent,Blue	VISCOSITY: Water Thin
FORM: Liquid	STORAGE(Unopened):..1 Year @R.T.
SCENT: Irritating	BIODEGRADABLE: ...Yes
pH: < 1	WEIGHT/GAL:9.0 lbs.
FLASH POINT: None	SHIPPING CLASS:8, Packing Gr II
FOAM: Medium	PACKAGING:5 gal(UN), 55 gal
TYPE: Hydroflouric Acid, 1st Step Truck Wash Concentrate	

