

GRIP STRIP CONTRACTOR

G1105005B

A highly active floor stripper that cuts multiple layers of burnished floor finish. This is a true no scrub/no rinse stripper that does not contain any caustic. This highly active formulation saves on labor costs as it quickly liquefies all floor finishes. This stripper is a must for all retail programs. Highly dilutable and low odor.



Where To Use

Vinyl Tile Vinyl Asbestos Asbestos Tile Linoleum
Concrete Rubber Terrazzo

Dilution

Heavy stripping – 1/8 (16 oz./gallon)

Medium – 1/16 (8 oz./gallon)

Light – 1/32 (4 oz./gallon)

Directions

Dust mop and scrape gum, etc. from floor. Determine dilution from table above and add appropriate amount of product to cool or room temperature water. Apply solution generously to a workable area. Allow solution to sit for 5-10 minutes. Floor must remain wet. For Mop-Wet Vacuum stripping system, the only agitation necessary will be from mopping action when applying the stripper. For floor machine stripping, agitate solution with a floor machine using an aggressive stripping pad (black or brown) if needed, hand scrub edges and corners with an edge pad or center of the scrubbing pad. Pick up solution and old finish with a wet vacuum. Inspect the entire floor to ensure that complete stripping had been accomplished. Reapply where necessary. Allow floor to dry completely prior to applying sealer or finish. Rinsing is not necessary but ensures a good, clean, residue free floor.

Technical Specifications

COLOR: Transparent	VISCOSITY: Water Thin
FORM: Liquid	STORAGE(Unopened):...1 Year @R.T.
SCENT: Pleasantly Scented	BIODEGRADABLE:Yes
pH: 11.5	WEIGHT/GAL:8.4
FLASH POINT: .None	SHIPPING CLASS:Not DOT Regulated
FOAM: Low	PACKAGING:5 gal bag in box
TYPE: Heavy Duty No Scrub-No Rinse Stripper Low Odor	



201 Boston Turnpike, Bolton, CT 06043-7203 800-227-5536 860-646-0172 FAX 860-645-6070

www.simoniz.com www.simonizjanitorial.com

All labels are GHS compliant.