

A revolutionary new polymer package formulated for a brilliant "off the mop gloss" that is long lasting. This unique chemistry results in a high gloss, long wearing, and quick curing sealer/finish. Although this product achieves a harder floor finish film, it can also be used in the most aggressive retail maintenance programs.



Where To Use

Vinyl Tile	Linoleum	Sealed Wood
Terrazzo	Rubber	Asbestos Tile
Asphalt Tile	Concrete	

Dilution

As is.

Directions

Prior to application, floor should be completely stripped of all old finish, scrubbed or cleaned. Follow stripping procedure from the Simoniz® Floor Care Manual. The floor should be completely dry before applying first coat and all subsequent coats. Apply in thin coats, evenly. If floor is old or in poor condition, two coats of Simoniz® Super Sealer are recommended. Then apply finish. On unsealed floors, apply 4-5 coats. On cleaned or scrubbed floors, apply as needed. Be sure to use a different mop for stripping, sealing and finish. Allow 24 hours for curing before burnishing.

Technical Specifications

COLOR:	Milk-white	TYPE:	Acrylic Polymer
FORM:	Liquid	SOLID CONTENT:	25% (+/- 1)
SCENT:	Mild Solvent/Polymer	INITIAL GLOSS:	High
pH:	8.0	RECOAT DRYING TIME:	<30 Minutes
FLASH POINT:	None	COVERAGE:	2500 - 3000 sq. ft.
FOAM:	None	LEVELING:	Excellent
VISCOSITY:	Water Thin	SLIP COEFFICIENT:	0.57
STORAGE(Unopened):	. 1 Year @R.T.	REMOVABILITY:	Excellent
BIODEGRADABLE:	Yes	SCUFF RESISTANCE:	Exceptional
WEIGHT/GAL:	8.6 @25° C	DETERGENT RESISTANT:	. Exceptional
SHIPPING CLASS:	None	HIGH SPEED BURNISH:	Yes
PACKAGING:	4x1, 5 gal, 55 gal		

