

A dilutable restorer used to maintain the fresh polished look between strippings and applications of floor finish. This high quality, dilutable product is used routinely for floor maintenance to keep the shine and the no-skid finish. Resist black marks.



Where To Use

Vinyl Tile	Asphalt Tile	Concrete that has been sealed
Vinyl Asbestos	Sealed Wood	Finished Stone Flooring
Linoleum		

Dilution

1/4 (32 oz./gallon)

Directions

Remove all gum and foreign materials. Sweep entire floor surface. Mop floor with AP-7 Neutral Floor Cleaner OR Sunshine Neutral Cleaner and allow to dry completely. Dilute Rebound (see above) into a clean mop bucket or use a plastic liner in bucket. Mop Rebound over entire floor and allow to dry. Buff to a high shine.

Technical Specifications

COLOR: Milk-white	TYPE: Dilutable Acrylic Polymer Restorer
FORM: Liquid	SOLID CONTENT: 16%
SCENT: Odorless	GLOSS: Excellent
pH: 8.0	RECOAT DRYING TIME: .. < 30 Minutes
FLASH POINT: None	COVERAGE: 10,000 sq. ft.
FOAM: None	LEVELING: Excellent
VISCOSITY: Water Thin	SLIP COEFFICIENT: Min. 0.5
STORAGE(Unopened): . 1 Year @R.T.	REMOVABILITY: Excellent
BIODEGRADABLE: Yes	SCUFF RESISTANCE: Good
WEIGHT/GAL: 8.5	DETERGENT RESISTANT: Good
SHIPPING CLASS: None	HIGH SPEED BURNISH: ... No
PACKAGING: 4x1, 5 gal, 55 gal	

